

Package ‘DEoptim’

January 2, 2012

Version 2.1-2

Title Global optimization by Differential Evolution

Author David Ardia, Katharine Mullen, Brian Peterson, Joshua Ulrich

Maintainer Katharine Mullen <katharine.mullen@nist.gov>

Description This package provides the DEoptim function which performs global optimization by differential evolution.

License GPL (>= 2)

Repository CRAN

Date/Publication 2011-11-21 16:18:16

R topics documented:

DEoptim	1
DEoptim-methods	6
DEoptim.control	9
SMI	13
xrrData	14

Index	15
--------------	-----------

DEoptim *Differential Evolution Optimization*

Description

Performs evolutionary global optimization via the Differential Evolution algorithm.

Usage

```
DEoptim(fn, lower, upper, control = DEoptim.control(), ...)
```

Arguments

fn	the function to be optimized (minimized). The function should have as its first argument the vector of real-valued parameters to optimize, and return a scalar real result. NA and NaN values are not allowed.
lower, upper	two vectors specifying scalar real lower and upper bounds on each parameter to be optimized, so that the i-th element of lower and upper applied to the i-th parameter. The implementation searches between lower and upper for the global optimum (minimum) of fn.
control	a list of control parameters; see <code>DEoptim.control</code> .
...	further arguments to be passed to fn.

Details

DEoptim performs optimization (minimization) of fn.

The control argument is a list; see the help file for `DEoptim.control` for details.

The R implementation of Differential Evolution (DE), **DEoptim**, was first published on the Comprehensive R Archive Network (CRAN) in 2005 by David Ardia. Early versions were written in pure R. Since version 2.0-0 (published to CRAN in 2009) the package has relied on an interface to a C implementation of DE, which is significantly faster on most problems as compared to the implementation in pure R. The C interface is in many respects similar to the MS Visual C++ v5.0 implementation of the Differential Evolution algorithm distributed with the book *Differential Evolution – A Practical Approach to Global Optimization* by Price, K.V., Storn, R.M., Lampinen J.A., Springer-Verlag, 2006, and found on-line at <http://www.icsi.berkeley.edu/~storn/>. Since version 2.0-3 the C implementation dynamically allocates the memory required to store the population, removing limitations on the number of members in the population and length of the parameter vectors that may be optimized. Since becoming publicly available, the package **DEoptim** has been used by several authors to solve optimization problems arising in diverse domains; see Mullen et al. (2011) for a review.

To perform a maximization (instead of minimization) of a given function, simply define a new function which is the opposite of the function to maximize and apply DEoptim to it.

To integrate additional constraints (than box constraints) on the parameters x of $fn(x)$, for instance $x[1] + x[2]^2 < 2$, integrate the constraint within the function to optimize, for instance:

```
fn <- function(x){
  if (x[1] + x[2]^2 < 2){
    r <- Inf
  } else{
    ...
  }
  return(r)
}
```

This simplistic strategy usually does not work all that well for gradient-based or Newton-type methods. It is likely to be alright when the solution is in the interior of the feasible region, but when the

solution is on the boundary, optimization algorithm would have a difficult time converging. Furthermore, when the solution is on the boundary, this strategy would make the algorithm converge to an inferior solution in the interior. However, for methods such as DE which are not gradient based, this strategy might not be that bad.

Note that `DEoptim` stops if any NA or NaN value is obtained. You have to redefine your function to handle these values (for instance, set NA to Inf in your objective function).

It is important to emphasize that the result of `DEoptim` is a random variable, i.e., different results will obtain when the algorithm is run repeatedly with the same settings. Hence, the user should set the random seed if they want to reproduce the results, e.g., by setting `set.seed(1234)` before the call of `DEoptim`.

`DEoptim` relies on repeated evaluation of the objective function in order to move the population toward a global minimum. Users interested in making `DEoptim` run as fast as possible should ensure that evaluation of the objective function is as efficient as possible. Using pure R code, this may often be accomplished using vectorization. Writing parts of the objective function in a lower-level language like C or Fortran may also increase speed.

Further details and examples of the R package **DEoptim** can be found in Mullen et al. (2011) and Ardia et al. (2011a, 2011b) or look at the package's vignette by typing `vignette("DEoptim")`. Also, an illustration of the package usage for a high-dimensional non-linear portfolio optimization problem is available by typing `vignette("DEoptimPortfolioOptimization")`.

Please cite the package in publications. Use `citation("DEoptim")`.

Value

The output of the function `DEoptim` is a member of the S3 class `DEoptim`. More precisely, this is a list (of length 2) containing the following elements:

`optim`, a list containing the following elements:

- `bestmem`: the best set of parameters found.
- `bestval`: the value of `fn` corresponding to `bestmem`.
- `nfeval`: number of function evaluations.
- `iter`: number of procedure iterations.

`member`, a list containing the following elements:

- `lower`: the lower boundary.
- `upper`: the upper boundary.
- `bestvalit`: the best value of `fn` at each iteration.
- `bestmemit`: the best member at each iteration.
- `pop`: the population generated at the last iteration.
- `storepop`: a list containing the intermediate populations.

Members of the class `DEoptim` have a `plot` method that accepts the argument `plot.type`. `plot.type = "bestmemit"` results in a plot of the parameter values that represent the lowest value of the objective function each generation. `plot.type = "bestvalit"` plots the best value of the objective function each generation. Finally, `plot.type = "storepop"` results in a plot of stored populations

(which are only available if these have been saved by setting the `control` argument of `DEoptim` appropriately). Storing intermediate populations allows us to examine the progress of the optimization in detail. A summary method also exists and returns the best parameter vector, the best value of the objective function, the number of generations optimization ran, and the number of times the objective function was evaluated.

Note

Differential Evolution (DE) is a search heuristic introduced by Storn and Price (1997). Its remarkable performance as a global optimization algorithm on continuous numerical minimization problems has been extensively explored; see Price et al. (2006). DE belongs to the class of genetic algorithms which use biology-inspired operations of crossover, mutation, and selection on a population in order to minimize an objective function over the course of successive generations (see Mitchell, 1998). As with other evolutionary algorithms, DE solves optimization problems by evolving a population of candidate solutions using alteration and selection operators. DE uses floating-point instead of bit-string encoding of population members, and arithmetic operations instead of logical operations in mutation. DE is particularly well-suited to find the global optimum of a real-valued function of real-valued parameters, and does not require that the function be either continuous or differentiable.

Let NP denote the number of parameter vectors (members) $x \in R^d$ in the population. In order to create the initial generation, NP guesses for the optimal value of the parameter vector are made, either using random values between lower and upper bounds (defined by the user) or using values given by the user. Each generation involves creation of a new population from the current population members $\{x_i \mid i = 1, \dots, NP\}$, where i indexes the vectors that make up the population. This is accomplished using *differential mutation* of the population members. An initial mutant parameter vector v_i is created by choosing three members of the population, x_{r_0} , x_{r_1} and x_{r_2} , at random. Then v_i is generated as

$$v_i \doteq x_{r_0} + F \cdot (x_{r_1} - x_{r_2})$$

where F is a positive scale factor, effective values for which are typically less than one. After the first mutation operation, mutation is continued until d mutations have been made, with a crossover probability $CR \in [0, 1]$. The crossover probability CR controls the fraction of the parameter values that are copied from the mutant. If an element of the trial parameter vector is found to violate the bounds after mutation and crossover, it is reset in such a way that the bounds are respected (with the specific protocol depending on the implementation). Then, the objective function values associated with the children are determined. If a trial vector has equal or lower objective function value than the previous vector it replaces the previous vector in the population; otherwise the previous vector remains. Variations of this scheme have also been proposed; see Price et al. (2006) and [DEoptim.control](#).

Intuitively, the effect of the scheme is that the shape of the distribution of the population in the search space is converging with respect to size and direction towards areas with high fitness. The closer the population gets to the global optimum, the more the distribution will shrink and therefore reinforce the generation of smaller difference vectors.

As a general advice regarding the choice of NP , F and CR , Storn et al. (2006) state the following: Set the number of parents NP to 10 times the number of parameters, select weighting factor $F = 0.8$ and crossover constant $CR = 0.9$. Make sure that you initialize your parameter vectors by

exploiting their full numerical range, i.e., if a parameter is allowed to exhibit values in the range $[-100, 100]$ it is a good idea to pick the initial values from this range instead of unnecessarily restricting diversity. If you experience misconvergence in the optimization process you usually have to increase the value for NP , but often you only have to adjust F to be a little lower or higher than 0.8. If you increase NP and simultaneously lower F a little, convergence is more likely to occur but generally takes longer, i.e., DE is getting more robust (there is always a convergence speed/robustness trade-off).

DE is much more sensitive to the choice of F than it is to the choice of CR . CR is more like a fine tuning element. High values of CR like $CR = 1$ give faster convergence if convergence occurs. Sometimes, however, you have to go down as much as $CR = 0$ to make DE robust enough for a particular problem. For more details on the DE strategy, we refer the reader to Storn and Price (1997) and Price et al. (2006).

Author(s)

David Ardia, Katharine Mullen <katharine.mullen@nist.gov>, Brian Peterson and Joshua Ulrich.

References

- Differential Evolution homepage: URL <http://www.icsi.berkeley.edu/~storn/code.html>.
- Ardia, D., Boudt, K., Carl, P., Mullen, K.M., Peterson, B.G. (2011) Differential Evolution with **DEoptim**. An Application to Non-Convex Portfolio Optimization. *The R Journal*, 3(1), 27-34. URL <http://journal.r-project.org/2011-1/>.
- Ardia, D., Ospina Arango, J.D., Giraldo Gomez, N.D. (2011) Jump-Diffusion Calibration using Differential Evolution. *Wilmott Magazine*, 55 (September), 76-79. URL <http://www.wilmott.com>.
- Mitchell, M. (1998) *An Introduction to Genetic Algorithms*. The MIT Press. ISBN 0262631857.
- Mullen, K.M, Ardia, D., Gil, D., Windover, D., Cline, J. (2011). **DEoptim**: An R Package for Global Optimization by Differential Evolution. *Journal of Statistical Software*, 40(6), 1-26. URL <http://www.jstatsoft.org/v40/i06/>.
- Price, K.V., Storn, R.M., Lampinen J.A. (2006) *Differential Evolution - A Practical Approach to Global Optimization*. Berlin Heidelberg: Springer-Verlag. ISBN 3540209506.
- Storn, R. and Price, K. (1997) Differential Evolution – A Simple and Efficient Heuristic for Global Optimization over Continuous Spaces, *Journal of Global Optimization*, 11:4, 341–359.

See Also

[DEoptim.control](#) for control arguments, [DEoptim-methods](#) for methods on DEoptim objects, including some examples in plotting the results; [optim](#) or [constrOptim](#) for alternative optimization algorithms.

Examples

```
## Rosenbrock Banana function
## The function has a global minimum f(x) = 0 at the point (1,1).
## Note that the vector of parameters to be optimized must be the first
```

```

## argument of the objective function passed to DEoptim.
Rosenbrock <- function(x){
  x1 <- x[1]
  x2 <- x[2]
  100 * (x2 - x1 * x1)^2 + (1 - x1)^2
}

## DEoptim searches for minima of the objective function between
## lower and upper bounds on each parameter to be optimized. Therefore
## in the call to DEoptim we specify vectors that comprise the
## lower and upper bounds; these vectors are the same length as the
## parameter vector.
lower <- c(-10,-10)
upper <- -lower

## run DEoptim and set a seed first for replicability
set.seed(1234)
DEoptim(Rosenbrock, lower, upper)

## increase the population size
DEoptim(Rosenbrock, lower, upper, DEoptim.control(NP = 100))

## change other settings and store the output
outDEoptim <- DEoptim(Rosenbrock, lower, upper, DEoptim.control(NP = 80,
  itermax = 400, F = 1.2, CR = 0.7))

## plot the output
plot(outDEoptim)

## 'Wild' function, global minimum at about -15.81515
Wild <- function(x)
  10 * sin(0.3 * x) * sin(1.3 * x^2) +
  0.00001 * x^4 + 0.2 * x + 80

plot(Wild, -50, 50, n = 1000, main = "'Wild function'")

outDEoptim <- DEoptim(Wild, lower = -50, upper = 50,
  control = DEoptim.control(trace = FALSE))

plot(outDEoptim)

DEoptim(Wild, lower = -50, upper = 50,
  control = DEoptim.control(NP = 50))

```

DEoptim-methods

DEoptim-methods

Description

Methods for DEoptim objects.

Usage

```
## S3 method for class 'DEoptim'  
summary(object, ...)  
## S3 method for class 'DEoptim'  
plot(x, plot.type = c("bestmemit", "bestvalit", "storepop"), ...)
```

Arguments

object	an object of class <code>DEoptim</code> ; usually, a result of a call to <code>DEoptim</code> .
x	an object of class <code>DEoptim</code> ; usually, a result of a call to <code>DEoptim</code> .
plot.type	should we plot the best member at each iteration, the best value at each iteration or the intermediate populations?
...	further arguments passed to or from other methods.

Details

Members of the class `DEoptim` have a `plot` method that accepts the argument `plot.type`. `plot.type = "bestmemit"` results in a plot of the parameter values that represent the lowest value of the objective function each generation. `plot.type = "bestvalit"` plots the best value of the objective function each generation. Finally, `plot.type = "storepop"` results in a plot of stored populations (which are only available if these have been saved by setting the `control` argument of `DEoptim` appropriately). Storing intermediate populations allows us to examine the progress of the optimization in detail. A `summary` method also exists and returns the best parameter vector, the best value of the objective function, the number of generations optimization ran, and the number of times the objective function was evaluated.

Note

Further details and examples of the R package **DEoptim** can be found in Mullen et al. (2011) and Ardia et al. (2011a, 2011b) or look at the package's vignette by typing `vignette("DEoptim")`.

Please cite the package in publications. Use `citation("DEoptim")`.

Author(s)

David Ardia, Katharine Mullen <katharine.mullen@nist.gov>, Brian Peterson and Joshua Ulrich.

References

Ardia, D., Boudt, K., Carl, P., Mullen, K.M., Peterson, B.G. (2011) Differential Evolution with **DEoptim**. An Application to Non-Convex Portfolio Optimization. *The R Journal*, 3(1), 27-34. URL <http://journal.r-project.org/2011-1/>.

Ardia, D., Ospina Arango, J.D., Giraldo Gomez, N.D. (2011) Jump-Diffusion Calibration using Differential Evolution. *Wilmott Magazine*, 55 (September), 76-79. URL <http://www.wilmott.com>.

Mullen, K.M, Ardia, D., Gil, D., Windover, D., Cline, J. (2011). **DEoptim**: An R Package for Global Optimization by Differential Evolution. *Journal of Statistical Software*, 40(6), 1-26. URL <http://www.jstatsoft.org/v40/i06/>.

See Also

[DEoptim](#) and [DEoptim.control](#).

Examples

```
## Rosenbrock Banana function
## The function has a global minimum  $f(x) = 0$  at the point (1,1).
## Note that the vector of parameters to be optimized must be the first
## argument of the objective function passed to DEoptim.
Rosenbrock <- function(x){
  x1 <- x[1]
  x2 <- x[2]
  100 * (x2 - x1 * x1)^2 + (1 - x1)^2
}

lower <- c(-10, -10)
upper <- -lower

set.seed(1234)
outDEoptim <- DEoptim(Rosenbrock, lower, upper)

## print output information
summary(outDEoptim)

## plot the best members
plot(outDEoptim, type = 'b')

## plot the best values
dev.new()
plot(outDEoptim, plot.type = "bestvalit", type = 'b', col = 'blue')

## rerun the optimization, and store intermediate populations
outDEoptim <- DEoptim(Rosenbrock, lower, upper,
                     DEoptim.control(itermax = 500,
                                     storepopfrom = 1, storepopfreq = 2))
summary(outDEoptim)

## plot intermediate populations
dev.new()
plot(outDEoptim, plot.type = "storepop")

## Wild function
Wild <- function(x)
  10 * sin(0.3 * x) * sin(1.3 * x^2) +
  0.00001 * x^4 + 0.2 * x + 80

outDEoptim = DEoptim(Wild, lower = -50, upper = 50,
                    DEoptim.control(trace = FALSE, storepopfrom = 50,
                                    storepopfreq = 1))

plot(outDEoptim, type = 'b')
```

```

dev.new()
plot(outDEoptim, plot.type = "bestvalit", type = 'b')

## Not run:
## an example with a normal mixture model: requires package mvtnorm
library(mvtnorm)

## neg value of the density function
negPdfMix <- function(x) {
  tmp <- 0.5 * dmvnorm(x, c(-3, -3)) + 0.5 * dmvnorm(x, c(3, 3))
  -tmp
}

## wrapper plotting function
plotNegPdfMix <- function(x1, x2)
  negPdfMix(cbind(x1, x2))

## contour plot of the mixture
x1 <- x2 <- seq(from = -10.0, to = 10.0, by = 0.1)
thexlim <- theylim <- range(x1)
z <- outer(x1, x2, FUN = plotNegPdfMix)

contour(x1, x2, z, nlevel = 20, las = 1, col = rainbow(20),
  xlim = thexlim, ylim = theylim)

set.seed(1234)
outDEoptim <- DEoptim(negPdfMix, c(-10, -10), c(10, 10),
  DEoptim.control(NP = 100, itermax = 100, storepopfrom = 1,
  storepopfreq = 5))

## convergence plot
dev.new()
plot(outDEoptim)

## the intermediate populations indicate the bi-modality of the function
dev.new()
plot(outDEoptim, plot.type = "storepop")

## End(Not run)

```

DEoptim.control

Control various aspects of the DEoptim implementation

Description

Allow the user to set some characteristics of the Differential Evolution optimization algorithm implemented in DEoptim.

Usage

```
DEoptim.control(VTR = -Inf, strategy = 2, bs = FALSE, NP = NA,
  itermax = 200, CR = 0.5, F = 0.8, trace = TRUE,
  initialpop = NULL, storepopfrom = itermax + 1,
  storepopfreq = 1, checkWinner = FALSE, avWinner = TRUE, p = 0.2,
  c = 0, reltol, steptol)
```

Arguments

VTR	the value to be reached. The optimization process will stop if either the maximum number of iterations <code>itermax</code> is reached or the best parameter vector <code>bestmem</code> has found a value <code>fn(bestmem) <= VTR</code> . Default to <code>-Inf</code> .
strategy	defines the Differential Evolution strategy used in the optimization procedure: 1: DE / rand / 1 / bin (classical strategy) 2: DE / local-to-best / 1 / bin (default) 3: DE / best / 1 / bin with jitter 4: DE / rand / 1 / bin with per-vector-dither 5: DE / rand / 1 / bin with per-generation-dither 6: DE / current-to-p-best / 1 any value not above: variation to DE / rand / 1 / bin: either-or-algorithm. Default strategy is currently 2. See <i>*Details*</i> .
bs	if <code>FALSE</code> then every mutant will be tested against a member in the previous generation, and the best value will proceed into the next generation (this is standard trial vs. target selection). If <code>TRUE</code> then the old generation and <code>NP</code> mutants will be sorted by their associated objective function values, and the best <code>NP</code> vectors will proceed into the next generation (best of parent and child selection). Default is <code>FALSE</code> .
NP	number of population members. Defaults to <code>NA</code> ; if the user does not change the value of <code>NP</code> from <code>NA</code> or specifies a value less than 4 it is reset when <code>DEoptim</code> is called as <code>10*length(lower)</code> . For many problems it is best to set <code>NP</code> to be at least 10 times the length of the parameter vector.
itermax	the maximum iteration (population generation) allowed. Default is 200.
CR	crossover probability from interval <code>[0,1]</code> . Default to 0.5.
F	step-size from interval <code>[0,2]</code> . Default to 0.8.
trace	Positive integer or logical value indicating whether printing of progress occurs at each iteration. The default value is <code>TRUE</code> . If a positive integer is specified, printing occurs every <code>trace</code> iterations.
initialpop	an initial population used as a starting population in the optimization procedure. May be useful to speed up the convergence. Default to <code>NULL</code> . If given, each member of the initial population should be given as a row of a numeric matrix, so that <code>initialpop</code> is a matrix with <code>NP</code> rows and a number of columns equal to the length of the parameter vector to be optimized.
storepopfrom	from which generation should the following intermediate populations be stored in memory. Default to <code>itermax + 1</code> , i.e., no intermediate population is stored.
storepopfreq	the frequency with which populations are stored. Default to 1, i.e., every intermediate population is stored.

checkWinner	logical value indicating whether to re-evaluate the objective function using the winning parameter vector if this vector remains the same between generations. This may be useful for the optimization of a noisy objective function. If checkWinner = TRUE and avWinner = FALSE then the value associated with re-evaluation of the objective function is used in the next generation. Default to FALSE.
avWinner	logical value. If checkWinner = TRUE and avWinner = TRUE then the objective function value associated with the winning member represents the average of all evaluations of the objective function over the course of the ‘winning streak’ of the best population member. This option may be useful for optimization of noisy objective functions, and is interpreted only if checkWinner = TRUE. The default value is TRUE.
p	when strategy = 6, the top (100 * p)% best solutions are used in the mutation. p must be defined in (0,1].
c	c controls the speed of the crossover adaptation. Higher values of c give more weight to the current successful mutations. c must be defined in (0,1].
reltol	relative convergence tolerance. The algorithm stops if it is unable to reduce the value by a factor of reltol * (abs(val) + reltol) after steptol steps. Defaults to sqrt(.Machine\$double.eps), typically about 1e-8.
steptol	see reltol. Defaults to itermax.

Details

This defines the Differential Evolution strategy used in the optimization procedure, described below in the terms used by Price et al. (2006); see also Mullen et al. (2009) for details.

- strategy = 1: DE / rand / 1 / bin.
This strategy is the classical approach for DE, and is described in DEoptim.
- strategy = 2: DE / local-to-best / 1 / bin.
In place of the classical DE mutation the expression

$$v_{i,g} = old_{i,g} + (best_g - old_{i,g}) + x_{r0,g} + F \cdot (x_{r1,g} - x_{r2,g})$$

is used, where $old_{i,g}$ and $best_g$ are the i -th member and best member, respectively, of the previous population. This strategy is currently used by default.

- strategy = 3: DE / best / 1 / bin with jitter.
In place of the classical DE mutation the expression

$$v_{i,g} = best_g + jitter + F \cdot (x_{r1,g} - x_{r2,g})$$

is used, where $jitter$ is defined as $0.0001 * rand + F$.

- strategy = 4: DE / rand / 1 / bin with per vector dither.
In place of the classical DE mutation the expression

$$v_{i,g} = x_{r0,g} + dither \cdot (x_{r1,g} - x_{r2,g})$$

is used, where $dither$ is calculated as $F + rand * (1 - F)$.

- strategy = 5: DE / rand / 1 / bin with per generation dither.
The strategy described for 4 is used, but $dither$ is only determined once per-generation.

- `strategy = 6`: DE / current-to-p-best / 1.
The top $(100 * p)$ percent best solutions are used in the mutation, where p is defined in $(0, 1]$.
- any value not above: variation to DE / rand / 1 / bin: either-or algorithm.
In the case that $\text{rand} < 0.5$, the classical strategy `strategy = 1` is used. Otherwise, the expression

$$v_{i,g} = x_{r0,g} + 0.5 \cdot (F + 1) \cdot (x_{r1,g} + x_{r2,g} - 2 \cdot x_{r0,g})$$

is used.

Several conditions can cause the optimization process to stop:

- if the best parameter vector (`bestmem`) produces a value less than or equal to VTR (i.e. $\text{fn}(\text{bestmem}) \leq \text{VTR}$), or
- if the maximum number of iterations is reached (`itermax`), or
- if a number (`steptol`) of consecutive iterations are unable to reduce the best function value by a certain amount ($\text{reltol} * (\text{abs}(\text{val}) + \text{reltol})$). $100 * \text{reltol}$ is approximately the percent change of the objective value required to consider the parameter set an improvement over the current best member.

Zhang and Sanderson (2009) define several extensions to the DE algorithm, including strategy 6, DE/current-to-p-best/1. They also define a self-adaptive mechanism for the other control parameters. This self-adaptation will speed convergence on many problems, and is defined by the control parameter `c`. If `c` is non-zero, crossover and mutation will be adapted by the algorithm. Values in the range of `c=.05` to `c=.5` appear to work best for most problems, though the adaptive algorithm is robust to a wide range of `c`.

Value

The default value of `control` is the return value of `DEoptim.control()`, which is a list (and a member of the S3 class `DEoptim.control`) with the above elements.

Note

Further details and examples of the R package **DEoptim** can be found in Mullen et al. (2011) and Ardia et al. (2011a, 2011b) or look at the package's vignette by typing `vignette("DEoptim")`. Also, an illustration of the package usage for a high-dimensional non-linear portfolio optimization problem is available by typing `vignette("DEoptimPortfolioOptimization")`.

Please cite the package in publications. Use `citation("DEoptim")`.

Author(s)

David Ardia, Katharine Mullen <katharine.mullen@nist.gov>, Brian Peterson and Joshua Ulrich.

References

Ardia, D., Boudt, K., Carl, P., Mullen, K.M., Peterson, B.G. (2011) Differential Evolution with **DEoptim**. An Application to Non-Convex Portfolio Optimization. URL *The R Journal*, 3(1), 27-34. URL <http://journal.r-project.org/2011-1/>.

Ardia, D., Ospina Arango, J.D., Giraldo Gomez, N.D. (2011) Jump-Diffusion Calibration using Differential Evolution. *Wilmott Magazine*, 55 (September), 76-79. URL <http://www.wilmott.com>.

Mullen, K.M, Ardia, D., Gil, D., Windover, D., Cline, J. (2011). **DEoptim**: An R Package for Global Optimization by Differential Evolution. *Journal of Statistical Software*, 40(6), 1-26. URL <http://www.jstatsoft.org/v40/i06/>.

Price, K.V., Storn, R.M., Lampinen J.A. (2006) *Differential Evolution - A Practical Approach to Global Optimization*. Berlin Heidelberg: Springer-Verlag. ISBN 3540209506.

Zhang, J. and Sanderson, A. (2009) *Adaptive Differential Evolution* Springer-Verlag. ISBN 978-3-642-01526-7

See Also

[DEoptim](#) and [DEoptim-methods](#).

Examples

```
## set the population size to 20
DEoptim.control(NP = 20)

## set the population size, the number of iterations and don't
## display the iterations during optimization
DEoptim.control(NP = 20, itermax = 100, trace = FALSE)
```

SMI

Swiss Market Index data

Description

See Mullen et al. (2011) for description of this dataset.

Usage

```
data("SMI")
```

References

Mullen, K.M, Ardia, D., Gil, D., Windover, D., Cline, J. (2011). **DEoptim**: *An R Package for Global Optimization by Differential Evolution*. *Journal of Statistical Software*, 40(6), 1-26. URL <http://www.jstatsoft.org/v40/i06/>.

xrrData	<i>X-ray reflectometry data</i>
---------	---------------------------------

Description

See Mullen et al. (2011) for description of this dataset.

Usage

```
data("xrrData")
```

References

Mullen, K.M, Ardia, D., Gil, D., Windover, D., Cline, J. (2011). **DEoptim**: *An R Package for Global Optimization by Differential Evolution*. Journal of Statistical Software, 40(6), 1-26. URL <http://www.jstatsoft.org/v40/i06/>.

Index

*Topic **datasets**

SMI, [13](#)

xrrData, [14](#)

*Topic **methods**

DEoptim-methods, [6](#)

*Topic **nonlinear**

DEoptim, [1](#)

DEoptim.control, [9](#)

*Topic **optimize**

DEoptim, [1](#)

DEoptim.control, [9](#)

constrOptim, [5](#)

DEoptim, [1](#), [7](#), [8](#), [11](#), [13](#)

DEoptim-methods, [5](#), [13](#)

DEoptim-methods, [6](#)

DEoptim.control, [2](#), [4](#), [5](#), [8](#), [9](#)

optim, [5](#)

plot.DEoptim (DEoptim-methods), [6](#)

SMI, [13](#)

summary.DEoptim (DEoptim-methods), [6](#)

xrrData, [14](#)

y (SMI), [13](#)