

Package ‘tiger’

February 15, 2012

Type Package

Title Time series of Grouped ERrors

Version 0.2.2

Date 2011-12-23

Author Dominik Reusser

Maintainer Dominik Reusser <reusser@pik-potsdam.de>

Description Temporally resolved groups of typical differences (errors) between two time series are determined and visualized

Depends R (>= 2.10.0), e1071, hexbin, qualV, klaR, som

License GPL-2

Repository CRAN

Date/Publication 2011-12-23 10:06:15

R topics documented:

tiger-package	2
change.order.clusters	3
color.factor	4
correlated	4
count.diff.direction.error	6
diagnostic	7
eD	8
example.peaks	9
include.others	10
k_hyd	11
k_rel	12
lagtime	13
LCS	14
nashS	14

plots	15
synth.peak.error	18
tiger	20
tiger.res	22
to.uniform	23
validityIndex	24

Index	26
--------------	-----------

tiger-package	<i>Time series of Grouped ERRors</i>
---------------	--------------------------------------

Description

About fifty performance measures are calculated for a gliding window, comparing two time series. The resulting matrix is clustered, such that each time window can be assigned to an error type cluster. The mean performance measures for each cluster can be used to give meaning to each cluster. Additionally, synthetic peaks are used to better characterize the clusters. The package provides functions to calculate and visualize these results.

Details

Use tiger to perform the calculations. See the package vignette for an example, how to perform calculations and how to evaluate information

Author(s)

Dominik Reusser

Maintainer: Dominik Reusser <dreusser@uni-potsdam.de>

References

Reusser, D. E., Blume, T., Schaeffli, B., and Zehe, E.: Analysing the temporal dynamics of model performance for hydrological models, *Hydrol. Earth Syst. Sci. Discuss.*, 5, 3169-3211, 2008.

Examples

```
data(tiger.example)
modelled <- tiger.single$modelled
measured <- tiger.single$measured
peaks <- synth.peak.error(rise.factor=2, recession.const=0.02, rise.factor2=1.5)
## Not run: result2 <- tiger(modelled=modelled, measured=measured, window.size=240, synthetic.errors=peaks)
errors.in.time(d.dates, result2, solution=6, show.months=TRUE)
## End(Not run)
```

change.order.clusters *Change numbering of clusters*

Description

Changes the cluster numbering in an fuzzy clustering object.

Usage

```
change.order.clusters(clustering, new.order)
```

Arguments

clustering	Object returned from cmeans
new.order	Vector with new cluster numbering.

Details

Cluster 1 from the old object is assigned the number stored in the first position in new.order, Cluster 2 the number on the second position and so on.

Value

Identical object as clustering except the cluster numbering is changed

Author(s)

Dominik Reusser

References

Reusser, D. E., Blume, T., Schaefli, B., and Zehe, E.: Analysing the temporal dynamics of model performance for hydrological models, Hydrol. Earth Syst. Sci. Discuss., 5, 3169-3211, 2008.

See Also

[cmeans](#) for the fuzzy clustering

Examples

```
data(tiger.example)

new.order <- c(6,3,2,5,4,1)

cmeans.result <- tiger.single$cluster.assignment[[6]]
str(cmeans.result)
cmeans.result2 <- change.order.clusters(cmeans.result, new.order)
```

`color.factor` *Create colors with intensity according to the magnitude of a value*

Description

Create colors with intensity according to the magnitude of a value

Usage

```
color.factor(color, value, max)
```

Arguments

<code>color</code>	The base color(s) to use
<code>value</code>	A vector of values
<code>max</code>	The maximum value represented by full intensity

Value

A vector of colors, one entry for each value

Author(s)

Dominik Reusser

Examples

```
data <- 1:10
cols=color.factor("red", data, max=10)
plot(data, col=cols)

cols=color.factor(c("red", "green", "blue"), data, max=10)
plot(data, col=cols)
```

`correlated` *Calculate correlation structure*

Description

Calculate the correlation structure between multiple performance measures

Usage

```
correlated(result, limit = 0.85, plot.scatter = FALSE, keep = NA)
correl(measures, limit = 0.85, plot.scatter = FALSE, keep = NA)
```

Arguments

result	object returned from tiger
measures	data.frame for which to determine correlation structure
limit	Limit for absolute correlation, above which data is considered to be correlated
plot.scatter	Boolean, indicating whether to show pairwise plots for correlated measures
keep	Vector with names of measures that must not be excluded because of correlation with other measures

Value

correl returns:

pairs	Matrix with indices of pairwise correlated measures
pairs.by.name	Matrix with measure names of pairwise correlated measures
possible.exclusion	List indicating which measures might be removed to end up with no strongly correlated measures. The list also indicates, which measure is correlated to the removed measures
to.drop	List of indices for measures to drop (according to previous list)
to.drop.by.name	List of measure names (of the previous list)

correlated returns a list of two correl results, one for the original performance measures and one for the transformed measures from a result from [tiger](#).

Author(s)

Dominik Reusser

See Also

This method helps to reduce the amount of data to be analyzed from an evaluation using [tiger](#)

Examples

```
data(tiger.example)
correlated <- correlated(tiger.single, keep=c("CE", "RMSE" ))
```

count.diff.direction.error
Compare sign of derivatives

Description

Counts the number of elements for which two vectors show different signs in the derivative.

Usage

```
count.diff.direction.error(x, y)
```

Arguments

x	First vector
y	Second vector

Value

```
sum((diff(x) / diff(y))<0, na.rm=T)
```

Author(s)

Dominik Reusser

See Also

[diagnostic_dawson](#)

Examples

```
#All different
count.diff.direction.error(1:10,10:1)

#One different
count.diff.direction.error(1:10,c(1:9, 8))
```

diagnostic

*Calculate a number of objectives to compare time series***Description**

`diagnostic_dawson` take two vectors (assumed to be time series) and calculates the following objective functions to compare them: correlation, Nash Sutcliffe efficiency, ratio of the integral, lagtime (maximum of the cross correlation), the number of timesteps with opposite sign of the derivative, the highest ratio between recession coefficients and the root mean square error, as well as the ones listed in Dawson 2007.

`diagnostic_window` calculates these measures for a part of the time series only. It is used internally by

`diagnostic_series` takes this a step further by calculating the above measures for a gliding window along the time series and calculating additional measures. Similar to `diagnostic`, the function takes two vectors (assumed to be time series) and calculates a number of objectives compare them. In contrast to the more simple `diagnostic`, the same objectives are applied to a gliding window and a few additional objectives are calculated: the ratio of the derivatives, the ratio of the recession coefficients for each time step and the current quantile of the residuals.

Usage

```
diagnostic_window(position, window.size, measured, modelled, use_qualV = FALSE, diff.ecdf=NA)
```

```
diagnostic_series(measured, modelled, window.size, step.size = 1, integral_correction = FALSE, use_qualV = FALSE)
```

```
diagnostic_dawson(modelled, measured, p=NA, m=NA, additional=TRUE, use_qualV=FALSE, diff.ecdf=NA )
```

Arguments

<code>modelled</code>	Modelled time series or array with dimension <code>c(number_series, dim(measured))</code>
<code>measured</code>	Measured time series
<code>position</code>	Index from where to start the calculation
<code>window.size</code>	Number of time steps to include
<code>step.size</code>	Size of the steps defining the number of scores to be calculating along the time series. For example, with a value of 5 every fifth value is included
<code>integral_correction</code>	Boolean. If true, the ratio of the integrals is divided by the total ratio of the entire integral. This way, relative integral errors can be detected.
<code>p</code>	The number of free parameters in each model - required to calculate AIC and BIC
<code>m</code>	The number of data points that were used in the model calibration - required to calculate AIC and BIC
<code>additional</code>	Boolean, indicating whether to calculate additional measures to the ones defined in Dawson 2007
<code>use_qualV</code>	Boolean, indicating whether to calculate the additional measures defined in Jachner 2007
<code>diff.ecdf</code>	ecdf -function of the bias (measured-modelled)

Details

For more details on the objectives, see the see-also-section

Value

A data frame with the described objectives

Author(s)

Dominik Reusser

References

Dawson, C. W.; Abrahart, R. J. & See, L. M. HydroTest: A web-based toolbox of evaluation metrics for the standardised assessment of hydrological forecasts *Environmental Modelling & Software*, 2007 , 22 , 1034-1052

Jachner, S.; van den Boogaart, K. G. & Petzoldt, T. Statistical Methods for the Qualitative Assessment of Dynamic Models with Time Delay (R Package qualV) *Journal of Statistical Software*, 2007 , 22 , 1-30

See Also

[qualVcor](#), [nashS](#), [lagtime](#), [count.diff.direction.error](#), [k_rel](#)

Examples

```
data(example.peaks, package="tiger")

plot(reference.peak, type="l")
lines(example.peaks[1,], lty=2)

diagnostic_dawson(measured = reference.peak, modelled = example.peaks[1,])

#first half only
diagnostic_window(measured=reference.peak, modelled=example.peaks[1,], position = 1, window.size = 45 )

#gliding window for 20 time steps
diagnostic_series(measured=reference.peak, modelled=example.peaks[1,], window.size = 20 )
```

Description

Calculate the euclidean distance for multiple vectors

Usage`eD(x, y)`**Arguments**

`x` matrix with first set of vectors.
`y` matrix with second set of vectors.

Details

`x` and `y` need the following structure to compare multiple vectors at once:
rows contain the `k` vectors
columns the `n` coordinates in the `n`-space
`str(x) == matrix [1:k, 1:n]`

Value

vector with the euclidean distance for each pair

Author(s)

Dominik Reusser

Examples`eD(1:3, 2:4)`

`example.peaks`*Synthetic peak errors*

Description

A number of synthetic peak errors used for testing performance measures and similar

Usage`data(example.peaks)`**Format**

The format for `example.peaks` is: num [1:12, 1:91] 0.1346 0.1346 0.1846 0.0846 0.1346 ...

The format for the `reference.peak` is: num [1:91] 0.135 0.134 0.134 0.134 0.134 ...

Examples

```
data(example.peaks)
str(example.peaks)
str(reference.peak)
plot(reference.peak,type="line")
lines(example.peaks[,1], lty=2)
diagnostic_dawson(measured = reference.peak, modelled = example.peaks[,1])
## maybe str(peaks) ; plot(peaks) ...
```

include.others

Internal Function: evaluate box plot

Description

Find clusters with a comparable position on the box plot with respect to the best value. Comparable position means the median of one set of values falls within the interquartile range of the reference set of values

Usage

```
include.others(selected, center, stats, best = FALSE)
```

Arguments

selected	index of the best value set.
center	where is the best value within the
stats	stats element of a boxplot result
best	are we comparing against the best set?

Value

Vector of indices for which elements are comparable

Author(s)

Dominik Reusser

See Also

[box.plots](#)

k_hyd	<i>Hydrological recession constant</i>
-------	--

Description

This function calculates the local hydrological recession constant for each point in a time series. The function returns NA for periods with increasing discharge.

Usage

```
k_hyd(x)
```

Arguments

x discharge time serie

Details

The function returns $-dx/dt * 1/x$ if dx/dt is larger than 0 and x is not 0. For the other cases, NA is returned.

Value

Vector of recession constants.

Author(s)

Dominik Reusser

References

Blume Recession Paper

See Also

[diagnostic_dawson](#)

Examples

```
data(example.peaks,package="tiger")
```

```
k_hyd(reference.peak)
```

k_rel	<i>Mean ratio of hydrological recession constants of two discharge time series</i>
-------	--

Description

This function calculates the mean ratio between local hydrological recession constant for each point in two discharge time series.

Usage

```
k_rel(x, y)
```

Arguments

x	discharge time serie
y	discharge time serie

Value

A scalar with the mean ratio

Author(s)

Dominik Reusser

See Also

[k_hyd](#), [diagnostic_dawson](#)

Examples

```
data(example.peaks, package="tiger")  
k_rel(reference.peak, example.peaks[1,])
```

lagtime	<i>Lagtime between two time series</i>
---------	--

Description

This function calculates the lagtime between x and y, defined as the shift resulting in the maximum cross correlation.

Usage

```
lagtime(x, y)
```

Arguments

x	Time series
y	Time series

Value

The lagtime as scalar. Positive if x is shifted towards later times.

Author(s)

Dominik Reusser

See Also

[ccf,diagnostic_dawson](#)

Examples

```
data(example.peaks,package="tiger")
plot(reference.peak, type="l")
lines(example.peaks[7,], lty=2)
lagtime(reference.peak, example.peaks[7,])
```

LCS *Longest common sequence*

Description

Faster implementation of the function provided by the qualV-package

Usage

```
LCS(a, b)
```

Arguments

a	first vector.
b	second vector.

Author(s)

Dominik Reusser

See Also

[LCS](#)

nashS *Calculates the (weighted) Nash Suttcliffe Efficiency coefficient*

Description

Calculates the Nash Suttcliffe Efficiency coefficient.

Usage

```
nashS(modelled, measured, weighth = NA)  
nashS_HF(modelled, measured, weighth = NA)
```

Arguments

modelled	Vector with modeled data
measured	Vector with measured data
weighth	If this vector is supplied, each data point is weighted accordingly

Details

The weighting corresponds to the value in the empirical cumulative distribution function.

Value

Returns a scalar between $-\infty$ and 1 corresponding to the agreement between measured and modelled data. 0 means the model agrees equally well as the mean value.

Author(s)

Dominik Reusser

References

http://en.wikipedia.org/wiki/Nash-Sutcliffe_efficiency_coefficient

Examples

```
ref.peak <- synth.peak(rise.factor=2, recession.const=0.02)
peak <- synth.peak(rise.factor=2, recession.const=0.03)
nashS(modelled=peak, measured=ref.peak)
```

plots

Evaluation plots for temporal dynamics of model performance

Description

Create various plot to understand the temporal dynamics of model performance

Usage

```
box.plots(result, solution, show.measures = 1:num.measures,
          new.order = 1:solution, show.synthetic.peaks = FALSE,
          synthetic.peaks.col = c(2:8, 2:8), show.timestep = NA,
          show.cell = NA,
          ref = NULL, ref.new.order = new.order, ref.solutions =
            solution, col.best.match = "black",
            clusterPalette = rainbow(solution))
errors.in.time(xval, result, solution, rain.data = NULL, show.months
              = FALSE, new.order = 1:solution, x.range =
              1:length(xval), pmax = max(c(result$measured,
              result$modelled), na.rm = TRUE), data.colors =
              data.frame(measured = c("grey"), modelled =
              c("black"), rain = c("black")), clusterPalette =
              rainbow(solution), color.cut.off = 0, frac.max = 0.7,
              frac.min = 0.4, grid.nx = 0, legend.pos = "topleft",
              show.data = TRUE, show.errors = TRUE, show.data.model
              = show.data, show.data.measured = show.data, ...)
peaks.in.clusters(result, solution, new.order = 1:solution)
peaks.on.som(result, solution, clusterPalette=rainbow(solution), cell.size = 0.9, mfrow=c(2,ceiling(n
som.cluster(result, maxc = result$maxc, solutions = 2:maxc, new.order = NA)
```

```

som.measure.level(result, show.measures = 1:num.measures, mfrow = c(4, 3))
peaks.measures(result, show.measures = 1:num.measures,
               synthetic.peaks.col = c(2:8, 2:8), mfrow = c(2, 3),
               col.best.match = "black", do.out = rep(TRUE,
               length(show.measures)), single.errors = FALSE,
               show.legend = TRUE, show.main = TRUE, y.range = NULL)
scatterplot(measures, show.measures=1:num.measures)
p.validityIndex(result, validity.max)

```

Arguments

result	object returned from tiger
measures	data.frame from which to create a scatter plot. e.g. result\$measures.uniform
solution	number of clusters to use for further evaluations (see also validityIndex)
show.measures	Vector with the indices of the performance measures to plot. Use result\$names[show.measures] to see the names of the measures
new.order	New numbering to assign to clusters. See also change.order.clusters
show.synthetic.peaks	Show values of the synthetic peaks on top of the box plots.
synthetic.peaks.col	Colors to use for synthetic peaks.
do.out	vector of booleans indicating whether to exclude outliers when showing the plot
cell.size	fraction of the cell square to be filled with color
show.cell	the scores for a certain cell on the SOM can be plotted as blue line on the box plot (see examples)
x.range	Indices of x-values to be plotted
y.range	Range for y axis
pmax	maximum discharge for definition of the plot range
frac.min	minimum of the y-range covered by color bars for cluster occurrence
frac.max	maximum of the y-range covered by color bars for cluster occurrence
clusterPalette	colors to use for the clusters
color.cut.off	Value of cluster occurrence below which the color bar is set to transparent (for better readability)
legend.pos	Position of the legend
data.colors	Color definition for rainfall and runoff
show.timestep	timestep for which the values for the performance measures are to be plotted as black lines in the box plot
xval	Values to be plotted on the x-axis (e.g. POSIX-date)
show.months	Boolean indicating whether to add month ticks to x axis
mfrow	see par
ref	Reference solution to be plotted in grey on the box plot

<code>ref.new.order</code>	New numbering to assign to clusters for reference solution on the box plot
<code>ref.solutions</code>	Number of clusters for reference solution for which to plot the box plot
<code>validity.max</code>	Do not plot solutions with cluster numbers resulting above in a validity index above <code>validity.max</code>
<code>col.best.match</code>	Color to use for plotting the line indicating the position of the best match
<code>rain.data</code>	vector with rainfall data
<code>show.data</code>	boolean, indicating whether to show discharge data
<code>show.data.measured</code>	boolean, indicating whether to show measured discharge data
<code>show.data.model</code>	boolean, indicating whether to show modeled discharge data
<code>show.errors</code>	boolean, indicating whether to show error type bars
<code>grid.nx</code>	number of grid lines to be plotted (see grid)
<code>maxc</code>	Highest number of clusters to be plotted
<code>solutions</code>	Vector of solutions to be plotted
<code>single.errors</code>	Boolean, indicating whether different synthetic errors should be combined into a single plot or shown in multiple plots
<code>show.legend</code>	Boolean, indicating whether to show the legend
<code>show.main</code>	Boolean, indicating whether to show performance measure names as plot title
<code>...</code>	additional parameters passed to plot

Details

`box.plots`: for each performance measure, a box plot is created showing the values for each cluster

`errors.in.time`: occurrence of the errors cluster along the time dimension

`peaks.in.clusters`: table of the position of the synthetic peak errors in the clusters.

`som.cluster`: Plot the location of the different clusters on the SOM for multiple numbers of clusters.

`som.measure.level`: Plot the distribution of the performance measures on the SOM.

`peaks.measures`: response of the performance measures to the synthetic peak errors.

`scatterplot`: scatter plot of the performance measures

See package vignette for further details about which plot does what.

Value

used for the side effect of plotting results

Author(s)

Dominik Reusser

References

Reusser, D. E., Blume, T., Schaepli, B., and Zehe, E.: Analysing the temporal dynamics of model performance for hydrological models, *Hydrol. Earth Syst. Sci. Discuss.*, 5, 3169-3211, 2008.

See Also

The package vignette

Examples

```
data(tiger.example)

new.order <- c(6,3,2,5,4,1)
correlated <- correlated(tiger.single, keep=c("CE","RMSE" ))

opar <- par(mfrow=c(3,5))
box.plots(tiger.single, solution=6, new.order=new.order, show.synthetic.peaks=TRUE)
box.plots(tiger.single, solution=6, new.order=new.order, show.cell=data.frame(x=1,y=1))
par(opar)
errors.in.time(xval=d.dates, result= tiger.single, solution=6, show.months=TRUE, new.order=new.order)
peaks.in.clusters(tiger.single, solution=6, new.order=new.order)
peaks.measures(tiger.single, show.measures=correlated$measures.uniform$to.keep)
scatterplot(tiger.single$measures.uniform, show.measures=correlated$measures.uniform$to.keep)
```

synth.peak.error

Generate synthetic peaks and peak errors

Description

These functions allow generation of synthetic hydrologic peaks generated from a combination of exponential functions. Also, synthetic errors for the reproduction of a reference peak can be generated in order to subsequently test the behaviour of performance measures with respect to these errors.

Usage

```
synth.peak(base = 0.07, base.time = 6, rise.time = 5, rise.factor,
recession.const = 0.2, length.out = 240, rez.time)
synth.peak.error(base = 0.07, base.time = 6, rise.time = 5,
rise.factor, rise.factor2, recession.const = 0.2, length.out = 240,
rez.time = length.out - base.time - rise.time, err1.factor = c(1.2,
1.4, 1.6), err2.factor = base/c(10, 5, 2), err3.factor = c(2, 4,
8), err4.factor = c(9, 18, 27), err5.factor = c(0.1, 0.2, 0.4),
err6.factor = c(0.7, 0.8, 0.9),
err9.factor = c(2, 3, 4.5))
p.synth.peak.error(peaks, y.max = (max(peaks, na.rm = TRUE)),
peak.cluster = NULL, peak.palette = grey(c(0, 0.6,
0.8)), use.layout = TRUE, show.errors = 1:n.errors,
peak.lty = rep(1, n.errors), mfrow = c(2,
ceiling(length(show.errors)/2)), plot.legend = TRUE,
print.error.nr = TRUE)
```

Arguments

base	level of the base flow component
base.time	number of time steps before the rise phase starts. May be negative, such that the peak starts outside the window.
rise.time	Number of time steps for the rise phase
rise.factor	The peak maximum is about <code>rise.factor</code> higher than the base flow.
rise.factor2	<code>rise.factor</code> for the "peaks" which only show a recession phase.
recession.const	Recession constant for the peak.
length.out	Total length of the time series to be returned.
rez.time	Length of the recession phase
err1.factor	Factors to use for the first error type: Over- and underestimation of the peak
err2.factor	Factors to use for the second error type: shifting of the entire time series
err3.factor	Factors to use for the third error type: Recession too fast/too slow
err4.factor	Factors to use for the fourth error type: Lag time
err5.factor	Factors to use for the fifth error type: Correct total volume, but peak over/underestimated
err6.factor	Factors to use for the sixth error type: Peak too wide/too narrow
err9.factor	Factors to use for the ninth error type: Shift during the recession phase
peaks	object returned from <code>synth.peak.error()</code>
y.max	upper limit for the y-axis
peak.cluster	object returned from <code>peaks.in.clusters</code> used for coloring the cluster assignment of synthetic peaks (see examples)
peak.palette	Colors to use if <code>peak.cluster</code> is NULL: first color for reference, second and third for peaks over- and underestimating the reference
use.layout	Boolean, indicating whether to use the predefined layout
plot.legend	Boolean, indicating whether to show the legend
print.error.nr	Boolean, indicating whether to label each subplot with a number
mfrow	mfrow plot parameter (only used, if <code>use.layout=FALSE</code>)
show.errors	Vector with indices indicating which errors to display
peak.lty	Line types for either clusters as defined in <code>peak.cluster</code> or as in <code>peak.palette</code>

Value

`synth.peak` returns a vector with the synthetic peak according to the provided parameters `synth.peak.error` returns an array with dimension 3. The first dimension corresponds to the error type. The second dimension to the level of the corresponding error type. The third dimension corresponds to the time.

Author(s)

Dominik Reusser

References

Reusser, D. E., Blume, T., Schaefli, B., and Zehe, E.: Analysing the temporal dynamics of model performance for hydrological models, *Hydrol. Earth Syst. Sci. Discuss.*, 5, 3169-3211, 2008.

See Also

The package vignette

Examples

```

ref.peak <- synth.peak(rise.factor=2, recession.const=0.02)
peaks <- synth.peak.error(rise.factor=2, recession.const=0.02, rise.factor2=1.5)
peaks2 <- synth.peak.error(rise.factor=2, recession.const=0.02,
  rise.factor2=1.5, err1.factor=c(1.3,1.5,2.0),
  err2.factor = c(0.02,0.03,0.06),
  err3.factor=c(2,4,10),
  err4.factor = c(9,22,40),
  err5.factor = c(0.2,0.3,0.5),
  err6.factor =c(2,3,5),
  err9.factor=c(1.5,3,6)
)

p.synth.peak.error(peaks)
p.synth.peak.error(peaks2)

data(tiger.example)
peak.cluster <- peaks.in.clusters(result=tiger.single, solution=5, new.order=c(2,3,5,1,4))
p.synth.peak.error(peaks=tiger.single$synthetic.errors, peak.cluster=peak.cluster, peak.palette=rainbow(5))

```

tiger

Calculate temporal dynamics of model performance

Description

About fifty performance measures are calculated for a gliding window, comparing two time series. The resulting matrix is clustered, such that each time window can be assigned to an error type cluster. The mean performance measures for each cluster can be used to give meaning to each cluster. Additionally, synthetic peaks are used to better characterize the clusters.

Usage

```

tiger(modelled, measured, window.size, step.size = 1,
  use.som = TRUE, som.dim = c(20, 20), som.init =
  "sample", som.topol = "hexa", maxc = 15,
  synthetic.errors = NA)
tiger.peaks(result, synthetic.errors)

```

Arguments

<code>modelled</code>	Time series of modelled data
<code>measured</code>	Time series of measured data
<code>window.size</code>	Size of the moving window
<code>maxc</code>	Maximum number of clusters to be tested
<code>synthetic.errors</code>	Matrix returned from synth.peak.error
<code>result</code>	object returned from <code>tiger</code>
<code>use.som</code>	boolean, indicating whether to use SOM before applying fuzzy clustering
<code>som.dim</code>	Dimension of the Self Organizing Map (SOM) $c(x,y)$
<code>som.init</code>	Method to initialize the SOM
<code>som.topol</code>	Topology of the SOM
<code>step.size</code>	Size of the steps defining the number of scores to be calculating along the time series. For example, with a value of 5 every fifth value is included

Details

See the package vignette.

Value

<code>maxc</code>	see input parameter
<code>window.size</code>	see input parameter
<code>modelled</code>	see input parameter
<code>measured</code>	see input parameter
<code>synthetic.errors</code>	see input parameter
<code>measures.synthetic.peaks</code>	matrix of performance measures for synthetic errors
<code>measures</code>	matrix of performance measures for the gliding time window
<code>na.rows</code>	vector of boolean, indicating which time windows contain NA values
<code>names</code>	names of the performance measures
<code>measures.uniform</code>	measures, transformed to uniform distribution
<code>measures.uniform.synthetic.peaks</code>	measures for synthetic errors, transformed with the corresponding transformation from previous item
<code>error.names</code>	names of the synthetic error types
<code>best.value.location</code>	list, indicating what the value for "no error" for each performance measure is
<code>validityMeasure</code>	vector with validty index for solutions with 2:maxc clusters
<code>cluster.assignment</code>	list of 2:maxc objects returned from cmeans

Author(s)

Dominik Reusser

References

Reusser, D. E., Blume, T., Schaefli, B., and Zehe, E.: Analysing the temporal dynamics of model performance for hydrological models, *Hydrol. Earth Syst. Sci. Discuss.*, 5, 3169-3211, 2008.

See Also

The package vignette

Examples

```

data(tiger.example)
modelled <- tiger.single$modelled
measured <- tiger.single$measured
peaks <- synth.peak.error(rise.factor=2, recession.const=0.02, rise.factor2=1.5)
## Not run: result2 <- tiger(modelled=modelled, measured=measured, window.size=240, synthetic.errors=peaks)
errors.in.time(d.dates, result2, solution=6, show.months=TRUE)
## End(Not run)

peaks2 <- synth.peak.error(rise.factor=2, recession.const=0.02,
  rise.factor2=1.5, err1.factor=c(1.3,1.5,2.0),
  err2.factor = c(0.02,0.03,0.06),
  err3.factor=c(2,4,10),
  err4.factor = c(9,22,40),
  err5.factor = c(0.2,0.3,0.5),
  err6.factor =c(2,3,5),
  err9.factor=c(1.5,3,6)
)

## Not run: result3 <- tiger.peaks(result2, peaks2)

peaks.in.clusters(result2, solution=6)
x11()
peaks.in.clusters(result3, solution=6)

## End(Not run)

```

tiger.res

Example data for TIGER package

Description

Example data for temppperform package

Usage

```
data(tiger.example)
```

Format

Object returned from `tiger`.

Source

Reusser, D. E., Blume, T., Schaefli, B., and Zehe, E.: Analysing the temporal dynamics of model performance for hydrological models, *Hydrol. Earth Syst. Sci. Discuss.*, 5, 3169-3211, 2008.

Examples

```
data(tiger.example)
errors.in.time(d.dates, tiger.multi, solution=6, show.months=TRUE)
```

to.uniform	<i>Transform data to uniform distribution</i>
------------	---

Description

Transform data to uniform distribution. Optionally, a set of values can be transformed against a reference set of data.

Usage

```
to.uniform(ref, val = NA)
```

Arguments

ref	Set of values that determine the transformation
val	Values to be transformed

Details

If values is NA, the reference set itself will be transformed.

Value

Vector with transformed values.

Author(s)

Dominik Reusser

Examples

```
a <- rnorm(100)
hist(a)
b <- to.uniform(a)
hist(b)
c <- to.uniform(ref=a, val=c(-0.5,0,0.5))
```

validityIndex

Validity Index for fuzzy clustering

Description

Calculate the validity index for fuzzy clusters. A validity index below 1 indicates, that in between clusters is larger than within clusters. Evaluating the validity index for various numbers of desired clusters may help to find the minimum.

Usage

```
validityIndex(cclust, values, verbose = FALSE)
```

Arguments

cclust	object returned from cmeans
values	data provided as x to cmeans
verbose	boolean. If true, values for numerator and denominator are printed.

Value

A single number, the validity index.

Author(s)

Dominik Reusser

References

Reusser, D. E., Blume, T., Schaeffli, B., and Zehe, E.: Analysing the temporal dynamics of model performance for hydrological models, *Hydrol. Earth Syst. Sci. Discuss.*, 5, 3169-3211, 2008.

Xie, X. and Beni, G.: A validity measure for fuzzy clustering, *IEEE T. Pattern Anal.*, 13, 841-847, 1991. 3181

See Also

[cmeans](#) for the fuzzy clustering itself

Examples

```
myOrig <- matrix(c(c(1,0,0,1),
                  c(0,0,1,2),
                  c(1,1,0,3)), nrow=3, ncol=4, byrow=TRUE)

myData <- rbind(
  matrix(myOrig[1,], nrow=50, ncol=4, byrow=TRUE),
  matrix(myOrig[2,], nrow=50, ncol=4, byrow=TRUE),
  matrix(myOrig[3,], nrow=50, ncol=4, byrow=TRUE)
)
str(myData)
myData[,1:3] <- myData[,1:3] + rnorm(3*150)*0.3
myData

maxc <- 10

require(e1071)
validity <- rep(NA, maxc)
all.cluster.rer <- list()
for(centers in 2:maxc){
  cluster.rer<-cmeans(x=myData, centers=centers, method="cmeans", m=2)
  validity[centers] <- validityIndex(cluster.rer , myData)
  all.cluster.rer[[centers]] <- cluster.rer
}

plot(validity, type="l")
```

Index

- *Topic **color**
 - color.factor, 4
- *Topic **datasets**
 - example.peaks, 9
 - tiger.res, 22
- *Topic **hplot**
 - plots, 15
 - synth.peak.error, 18
- *Topic **package**
 - tiger-package, 2
- *Topic **univar**
 - nashS, 14
- *Topic **utilities**
 - change.order.clusters, 3
 - correlated, 4
 - count.diff.direction.error, 6
 - diagnostic, 7
 - eD, 8
 - include.others, 10
 - k_hyd, 11
 - k_rel, 12
 - lagtime, 13
 - LCS, 14
 - nashS, 14
 - plots, 15
 - synth.peak.error, 18
 - tiger, 20
 - to.uniform, 23
 - validityIndex, 24
- box.plots, 10
- box.plots (plots), 15
- ccf, 13
- change.order.clusters, 3, 16
- cmeans, 3, 21, 24
- color.factor, 4
- cor, 8
- correl (correlated), 4
- correlated, 4
- count.diff.direction.error, 6, 8
- d.dates (tiger.res), 22
- diagnostic, 7
- diagnostic_dawson, 6, 11–13
- diagnostic_dawson (diagnostic), 7
- diagnostic_series (diagnostic), 7
- diagnostic_window (diagnostic), 7
- ecdf, 7
- eD, 8
- errors.in.time (plots), 15
- example.peaks, 9
- grid, 17
- include.others, 10
- k_hyd, 11, 12
- k_rel, 8, 12
- lagtime, 8, 13
- LCS, 14, 14
- nashS, 8, 14
- nashS_HF (nashS), 14
- p.synth.peak.error (synth.peak.error), 18
- p.validityIndex (plots), 15
- par, 16
- peaks.in.clusters, 19
- peaks.in.clusters (plots), 15
- peaks.measures (plots), 15
- peaks.on.som (plots), 15
- plots, 15
- qualV, 8
- reference.peak (example.peaks), 9
- scatterplot (plots), 15

som.cluster (plots), [15](#)
som.measure.level (plots), [15](#)
synth.peak (synth.peak.error), [18](#)
synth.peak.error, [18](#), [21](#)

tiger, [5](#), [16](#), [20](#), [23](#)
tiger-package, [2](#)
tiger.example (tiger.res), [22](#)
tiger.multi (tiger.res), [22](#)
tiger.res, [22](#)
tiger.single (tiger.res), [22](#)
to.uniform, [23](#)

validityIndex, [16](#), [24](#)